		Quotation Signature
	Customer Ref.	User's weight Kg
Dealer	PAGE 1/ May 2024	
Key □ standard	IDRA2.0	
☐ IDRA2.0 Fix axle ☐ IDR	RA 2.0 Adj axle	Aluminium rigid frame
HS Back-rest height	40	SH SH mwith P=40 cm
☐ Pearl white ☐ Pearl red ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	Ck-rest: Seat: Tension adj nylon ☐ Fix (standa Breathable tension adj ☐ Tension Without any backrest upholstery → #AMEKH (separate order form)	n adj. (velcro) Colours: orange, řed, green, cornflower, light blue Coloured (breathable)
Single tubular footplate 4 Open O Carbon fibre O Tilt adjustable Carbon fibre closed	Push handles Without Fixed pushing handles pushing handles	O Height adjustable pushing handles O Foldable pushing handles
Distance between the hub centre and backrest	Backrest tilt 7	Front angle 8 Rear 9 wheel camber
9 cm (standard)	91° 89° 91° (standard) 93°	☐ Quick rel.axles Ø 12mm with cambered bushes length 42 mm (default) ☐ Quick rel. axles Ø 1/2" (12,7mm) w/42mm bushes ☐ Quick rel. axles Ø 1/2" (12,7mm) w/42mm bushes ☐ Quick rel. axles Ø 1/2" (12,7mm) w/50mm bushes
Side guards Aluminium with carbon fibre wing Aluminium with straight carbon fibre	Classic (30 cm long)	Brakes Scissor brake Composite Standard Pull brake Ceft Standard Ceft Ceft Standard Ceft Ceft Standard Ceft Ceft Standard Ceft Ceft Ceft Standard Ceft Ceft Ceft Standard Ceft Ceft Ceft Standard Ceft Ceft Ceft Ceft Ceft Standard Ceft Ceft Ceft Ceft Ceft Ceft Standard Ceft Ceft
Notes		

Dealer		OFFCARR		Order N° Date Customer Ref.			
		AO MINISTRA		PAGE 2/2 May 2024		IDRA2.0	
Rear wheels	Pushri	ims	15	Spokes guards	16	Front castors	
□ 24" Ultralight (24 spokes) □ 24" Light (24 spokes) □ 24" Star 6x3 (18 spokes, silver or black) □ 24" (36 spokes) □ 24" Mountain-bike with Citybike tyre □ 24" Mountain-bike with Offroad tyre ○ 24" Spinergy LX spokes colour(black def.) ○ 25" Spinergy LX spokes colour(black def.) ○ 25" Light (24 spokes) black Tyres □ Pneum. Marathon Plus □ Pneum. high pressure Smooth □ Pneum. high pressure Plugged 24" □ Pn.Schwalbe Right Run 24" ○ Solid black KIK 24" not available for Ultralight wheels	O Rubber O Titanium O OVAAL O OVAAL O CarboLi O CL Curvel O CL Quac O CarboLi O Silicon C	um dark m-plated steel 24' coated n (silver aluminium 6 (dark aluminium G (w/sil.insert) fe CURVE L 24" TetraGrip rubb.c.: dro rubber ctd 24' fe GEKKO 24" *	n) * * ** ** ** ** ** ** ** ** ** ** ** *	O Transparent 24" O Black 24" O Fantasy code pattern (see catalogue of spokeg) Lined cushion in foam polyurethat O 3 cm high O 5 cm high	uards)	 □ 80 (3") solid ○ 80 (3") solid with lights □ 100 (4"x1.1/4) solid with plastic rim ○ 100 (4"x1) solid with lights □ 100 (4"x1.1/4) solid with alum. rim □ 125 (5"x1.1/4) solid with plastic rim □ 125 (5"x1.1/4) solid with alum. rim ○ 125 (5"x1) solid with lights □ 150 (6") pneumatic □ 150 (6") solid 	
Pockets Anodized set (Rear wheel rims & hubs sideguard supports, forkst) Small under the fix seat or Small hanging from the seat Black Silver Light blue Red Orange Cyclamen light purple (only 24" Light Backrest bar Standard: P(bar) 7,5cm; P			s and fittings)	Options 23 "M+F" velcro strips (hook and loop) on seat 24 "M" velcro strips (hook) on seat 25 "F" velcro strips (loop) on seat 26 Padded rigid seat cushion h 5 27 Chest harness 28 Chest belt 29 Abductor belt 30 Catheter holder pocket 31 Rx OLx Crutch holder 32 O Pump for pneumatics 33 Suitcase holder 34 45° pelvic belt 35 45° padded pelvic belt 36 O Black backpack 37 O Front protective covers			
STANDARD SEAT "Y" SHAPED FRONT FRAME (stand.)		O ERGO SHAPED NT FRAME		STRAIGHT FRONT FRAME	Notes		